



QL40

Stackable Logging Tools

QL Stackable Logging Tools

The Quick Link (QL) series of slim-hole logging tools can be combined in custom configurations to acquire more data in a single logging pass.

Each QL tool can be used as a stand-alone probe or combined into a “string” or “stack” to yield multiple measurement parameters simultaneously.

This innovative flexibility saves time in field acquisition and allows for purchases to suit budgets and projects, as needed.



Examples of QL Logging Tool Applications in Mining, Water, Engineering and Energy

Lithology identification ▶ QL40 GR · QL40 OBI · QL40 DEN · QL40 NEU · QL40 FWS · QL40 ELOG · QL40 IND

Mineral exploration ▶ QL40 GR · QL40 SGR · QL40 IP · QL40 HM-453 · QL40 IND · QL40 DEN

Stratigraphy and bed thickness ▶ QL40 GR · QL40 OBI · QL40 DEN · QL40 NEU · QL40 FWS · QL40 ELOG

Permeable zones and Porosity ▶ QL40 DEN · QL40 FWS · QL40 ELOG · QL40 NEU

Location of aquifers / aquitards ▶ QL40 FTC · QL40 SFM · QL40 IND

Density ▶ QL40 DEN

Water quality and contamination ▶ QL40 FTC

Fluid flow measurements ▶ QL40 SFM

Detection of weathered, fractured and permeable zones ▶ QL40 DEN · QL40 IND · QL40 FWS · QL40 ABI
QL40 OBI · QL40 FTC · QL40 NEU

Fracture identification and orientation ▶ QL40 ABI · QL40 OBI

Core orientation ▶ QL40 ABI · QL40 OBI

Local Stress (borehole breakout orientation) ▶ QL40 ABI · QL40 OBI · QL40 CAL

Rock Strength and elastic parameters ▶ QL40 DEN · QL40 FWS · QL40 ABI

Coal quality ▶ QL40 DEN · QL40 GR · QL40 ELOG

Cased hole integrity / cementation ▶ QL40 GR-CCL · QL40 ABI · QL40 FWS

Borehole shape, volume, integrity and orientation ▶ QL40 ABI · QL40 OBI · QL40 CAL · QL40 DEV



Imaging Tools

QL40 ABI™/ABI™ VLB Acoustic Televiewer

- Sensor**
Ultrasonic Transducer
- Temperature - Pressure**
0-70°C (32-158°F)
200 bar (2900 psi)
- Borehole diameter**
0.05 – 0.50 m (2"– 20")
depending on borehole conditions
- Diameter - Length**
40 mm (1.6") - 1.62 m (63")
- Weight**
6.5 kg (14.38 lbs)
- Measurements/Features**
- 360° orientated acoustic image (amplitude & travel time)
 - Borehole azimuth and tilt
 - Tool internal temperature
 - Relative bearing
 - Magnetic field / Gravity
 - 3 accelerometer/
3 magnetometer calibrated components
 - QL40 ABI VLB specifics
 - Casing thickness integrity
 - CADI (cement amplitude decay index) qualitative cement impedance

QL40 OBI™/OBI™ UV Optical Televiewer

- Sensor**
1/3" high sensitivity CMOS digital image sensor
- Temperature - Pressure**
0-70°C (32-158°F)
200 bar (2900 psi)
- Borehole diameter**
0.05-0.53 m (2"-21") depend-
ing on borehole conditions
- Diameter - Length**
40 mm (1.6") - 1.47 m (57.9")
- Weight**
5.3 kg (11.7 lbs)
- Measurements/Features**
- 360° RGB true color oriented image
 - UV light option (UVA-365 nm)
 - Borehole azimuth and tilt
 - Relative bearing
 - Magnetic field / Gravity
 - Gravity
 - 3 accelerometer/
3 magnetometer calibrated components
 - Temperature of CMOS image sensor

Sonic Tool

QL40 FWS-S Full Waveform Sonic

- Sensor**
Ceramic piezoelectric
- Temperature - Pressure**
0-70°C (32-158°F)
200 bar (2900 psi)
- Diameter - Length**
50 mm (2")
2.27m (89.4") (1Tx-4Rx configuration)
- Weight**
18 kg (39.7 lbs)
- Measurements/Features**
- Monopole 15 KHz resonant frequency
 - Full waveform per receiver
 - Real time p-wave velocity or slowness
 - Real time CBL processing
 - Additional post processing module available in WellCAD

○ Bottom ● In line

Mechanical Tool

QL40 CAL 3 Arm Caliper

- Temperature - Pressure**
0-70°C (32-158°F)
200 bar (2900 psi)
- Diameter - Length**
42.3 mm (1.67") - 1.78 m (70.28")
- Weight**
9.04 kg (19.93 lbs)
- Measurements/Features**
- Calibrated measurement of borehole diameter in inches, centimeters or millimeters
 - Easy exchangeable short and long caliper arms and wear tips

Magnetic Tool

QL40 HM-453 Magnetic Susceptibility

- Sensor**
W-R : Two coil system with inter coil spacing of 25 cm operating at ~ 2Khz
- Temperature - Pressure**
0-70°C (32-158°F)
200 bar (2900 psi)
- Diameter - Length**
W-R :
44.6 mm (1.75") - 1.54 m (60.6")
- Weight**
W-R : 7 kg (15.4 lbs)
- Measurements/Features**
W-R : Magnetic susceptibility in 10e⁻³ Si

Deviation Tool

QL40 DEV Borehole Deviation

- Sensor**
APS544-3 axis magnetometer and accelerometer
- Temperature - Pressure**
0-70°C (32-158°F)
200 bar (2900 psi)
- Diameter - Length**
40 mm (1.6") - 0.7 m (28")
- Weight**
3.4 kg (7.5 lbs)
- Measurements/Features**
- Angular values of azimuth, tilt and relative bearing
 - Calibrated values of each accelerometer and magnetometer components

Fluid Properties Tools



QL40 SFM

Bi-directional spinner Flowmeter

Temperature - Pressure
0-70°C (32-158°F)
200 bar (2900 psi)

Diameter - Length
40 mm (1.6") excluding cage
0.9 m (35.4")

Weight
3.2 kg (7.05 lbs)

Measurements/Features

- 50mm (2") diameter impeller cage
- 75mm (3") diameter impeller cage
- 100mm (4") diameter impeller cage
- Spinner speed in cps up and down



QL40 FTC-I & FTC-B

Fluid Temperature and Conductivity

Temperature - Pressure
0-70°C (32-158°F)
200 bar (2900 psi)

Diameter - Length
Bottom sub :
40mm (1.6") - 0.78m (30.7")
In line sub :
50mm (2") - 0.94m (37")

Weight
Bottom sub : 3.3kg (7.27lbs)
In line sub : 6.2kg (13.6lbs)

Measurements/Features

- Fluid temperature in °C
- Fluid conductivity in µS/cm or mS/cm
- Compensated conductivity at 25°C in µS/cm or mS/cm

○ Bottom ● In line

Electrical Tools



QL40 ELOG

Normal Resistivity (8", 16", 32", 64", SP & SPR)

Temperature - Pressure
0 -70°C (32-158°F)
200 bar (2900 psi)

Diameter - Length
40 mm (1.6")
1.89 m (74.57")

Weight
8.8 kg (19.4 lbs)

Measurements/Features

- 8", 16", 32" and 64" Normal Resistivity in [Ohm-m]
- SP in [mV]
- SPR in [Ohm]
- Current [mA]

Bridles
QL40 IS 1
QL40 IS 2
QL40 IS 4



QL40 IP

Induced Polarization and Normal Resistivity (8", 16", 32", 64", SP & SPR)

Temperature - Pressure
0-70°C (32-158°F)
200 bar (2900 psi)

Diameter - Length
40 mm (1.6")
1.89 m (74.57")

Weight
8.8 kg (19.4 lbs)

Measurements/Features

- Chargeability Ma in [ms] on 16" and 64" electrodes
- 2 spacing full wave data
- 8", 16", 32" and 64" Normal Resistivity in [Ohm-m]
- SP in [mV]
- SPR in [Ohm]

Bridles
QL40 IS 1
QL40 IS 2
QL40 IS 4



QL40 IND

Dual Induction Probe

Sensor
Dual coil system with intercoil spacing : 50 & 80 cm
Operating Frequency : 100 kHz

Temperature - Pressure
0-70°C (32-158°F)
200 bar (2900 psi)

Diameter - Length
45 mm (1.77")
1.94 m (76.38")

Weight
5.1 kg (11.24 lbs)

Measurements/Features

- Medium Induction : mS/m
- Deep Induction : mS/m

Nuclear Tools - Passive



QL40 GR

**Total Count
Natural Gamma**

Sensor
NaI (TI) crystal (0.875 x 3.0")

Temperature - Pressure
0-70°C (32-158°F)
200 bar (2900 psi)

Diameter - Length
40 mm (1.6") - 1.03 m (40.43")

Weight
4.15 kg (9.15 lbs)

Measurements/Features

- Total gamma counts in CPS and/or API unit



QL40 GR-CCL

**Natural Gamma &
Casing Collar Locator**

Sensor
GR: NaI (TI) crystal (1 x 3")
CCL: 32 x 280 mm coils & magnets assembly

Temperature - Pressure
0-70°C (32-158°F)
200 bar (2900 psi)

Diameter - Length
40 mm (1.6") - 1.16 m (46")

Weight
6.0 kg (13.23 lbs)

Measurements/Features

- Total gamma counts in CPS and/or API unit
- CCL in mV



QL40 SGR

**Natural
Spectral Gamma**

Sensor
CeBr3 crystal (0.79 x 3.78")
BGO crystal (1 x 4")

Temperature - Pressure
0-70°C (32-158°F)
200 bar (2900 psi)

Diameter - Length
40 mm (1.6") - 1.01 m (39.8")

Weight
6 kg (13.2 lbs)

Measurements/Features

- Up to 512 channels spectrum (BGO)
- Up to 2048 channels spectrum (CeBr3)
- Spectrum stabilized (software)
- Nuclides concentrations
- Window gamma counts
- Total gamma counts in CPS and/or API unit

☐ Bottom ☒ In line

Nuclear Tools - Active



QL40 DEN

**Formation Density
Sonde**

Sensor
CSI (TI) crystals
SSD (20cm) and
LSD (35cm)

Temperature - Pressure
0-70°C (32-158°F)
200 bar (2900 psi)

Diameter - Length
51 mm (2.01") - 1.83 m (72.24")

Weight
19.2 kg (42.33 lbs)

Measurements/Features

- SSD : in CPS
- LSD : in CPS
- SSD density : in g/cc
- LSD density : in g/cc
- Compensated density (RHOB) : in g/cc
- Compensation (DRHO) : in g/cc
- Caliper : in mm or inch



QL40 NEU

**Neutron - Thermal
Neutron**

Sensor
Single He-3 thermal neutron detector
35 cm source-detector spacing

Temperature - Pressure
0-70°C (32-158°F)
200 bar (2900 psi)

Diameter - Length
40 mm (1.6") - 1.32m (51.97")

Weight
6.3 kg (13.89 lbs)

Range
0 - 100.000 CPS

Measurements/Features

- Qualitative measurement of formation porosity in open and cased holes. Measures hydrogen content of formation.



Advanced Logic Technology

info@alt.lu

www.alt.lu

ALT headquarters

Zoning de Solupla
30H Rue de Niederpallen
L-8506 Redange
Luxembourg
T. +352 28 56 151

ALT Asia

36th Floor, Menara Maxis
Kuala Lumpur City Centre
50088 Kuala Lumpur
Malaysia
T. +60 3 2615 7261



sales@mountsopris.com

www.mountsopris.com

Mount Sopris Instrument Co.

4975 East 41st Avenue
Denver,
Colorado 80216
USA
T. +(1) 303 279 3211